

ALABAMA DEPARTMENT OF TRANSPORTATION

AERONAUTICS BUREAU 1409 COLISEUM BOULEVARD MONTGOMERY, ALABAMA 36110 PHONE (334) 242-6820 FAX (334) 353-6540



January 24, 2011

Ms. Misty Jones, Manager South Alabama Regional Airport 21861 Bill Benton Lane Andalusia, Alabama 36421

Subject:

Annual Inspection Report

South Alabama Regional Airport

Dear Ms. Jones:

An inspection of the South Alabama Regional Airport was conducted by personnel of the Alabama Department of Transportation Aeronautics Bureau on January 7, 2011. The purpose of the inspection was to update the information currently on file regarding the airport and to ascertain compliance with the rules and regulations of the Alabama Department of Transportation governing licensed public-use airports within the State of Alabama.

Attached you will find a copy of the Annual Inspection Report for the airport. As noted in the report, the airport meets the requirements for the issuance of an operating license. The report also details a maintenance item with the runway surface that should be addressed.

If you should have any questions concerning the inspection or corrective actions, please do not hesitate to contact the Aeronautics Bureau at (334) 242-6820.

Sincerely,

John C. Eagerton IV, D.P.A. Chief. Aeronautics Bureau

Copy: Mr. Rans Black FAA/ADO

Mr. Keith Shippey BWSC-Dothan

JANUARY 7, 2011



ANNUAL INSPECTION REPORT



SOUTH ALABAMA REGIONAL AIRPORT
AT BILL BENTON FIELD
ANDALUSIA, ALABAMA

TABLE OF CONTENTS

INTRODUCTION	PAGE 1	1
INSPECTION METHODOLOGY	PAGE 1	1
LICENSE STATUS	PAGE 2	2
APPROACH / DEPARTURE PATHS	PAGE 2	2
PRIMARY SURFACE	PAGE 4	1
RUNWAY SAFETY AREA	PAGE 4	1
AIRPORT MARKINGS	PAGE 5	5
WIND DIRECTION INDICATOR	PAGE 6	5
AIRPORT LIGHTING	PAGE 7	7
RUNWAY, TAXIWAY AND APRON CONDITIONS	PAGE 8	3
FUELING AREA REQUIREMENTS	PAGE 8	3
PROHIBITED ACTIVITIES	PAGE 9)
SUMMARY	PAGE 10)
APPENDIX 1	PAGE 11	l
AIRPORT SAFETY SELF-INSPECTION CHECKLIST		

January 7, 2011

Introduction:

<u>Code of Alabama 23-1-357(c)</u>. The department may perform such acts, issue and amend such orders and make, promulgate, or amend general or special rules, regulations, and procedures and establish minimum standards, consistent with the provisions of this article as it shall deem necessary to carry out the provisions of this article and to perform its duties hereunder, all commensurate with and for the purpose of protecting and insuring the general public interest, health, welfare, and safety. (Act 2000-220, 10.)

In accordance with the provisions of the Code of Alabama 23-1-357(c) an inspection of the SARA at Bill Benton Field was conducted by Mr. Kline Jeffcoat of the Alabama Department of Transportation Aeronautics Bureau on January 7, 2011.

The corrective actions that may be prescribed in this inspection report do not relieve the airport owner from compliance with any other Federal, State or local laws, ordinances or regulations that may be applicable. It is the responsibility of the airport owner to be aware of and obey all Federal, State or local laws, ordinances or regulations that may have a bearing on the corrective actions that may be specified in this report.

Inspection Methodology:

The inspection of the required State Approach/Departure Path and Federal Runway Protection Zones was accomplished by the use of approved engineering methods and equipment. The angles, locations and heights of trees or other objects within these areas were derived by the use of a Theodolite and electronic distance measuring device.

All other areas of the inspection were conducted visually and photographed for reference purposes.

The FAA Airport Design Standards referred to in this report were taken from the Airport Layout Plan (ALP) dated November 2005.

January 7, 2011

License Status:

Code of Alabama 23-1-375(a). ...a person or municipality may not operate an airport, restricted landing area, or other air navigation facility without a license issued by the department.

Based upon the findings of the inspection conducted on January 7, 2011, it was determined that the airport *meets* the requirements for the issuance of an operating license.

The inspection was conducted on the airport under the provisions of the Administrative Code for the following areas:

1. Approach and Departure Paths
Administrative Code 450-9-1-.12(1)
(See Appendix 1)

State Licensing Standards:

- For all hard surface runways the approach and departure path begins 200 feet from the runway end (runway threshold).
- The approach and departure path for all runways is centered along the extended runway centerline and extends for 1000 feet.
- The approach and departure path for all runways slopes up at a ratio of 20:1.
- All penetrations of the approach and departure paths, whether natural or manmade, constitute an obstruction to navigation and must be removed.
- The land beneath the approach and departure path must be controlled by the airport owner. This is accomplished by ownership of the property in fee simple or by written perpetual agreement with the owner of the land.

Inspection Results:

- Runway 11: No obstructions (Photo # 1)
- Runway 29: No obstructions (Photo # 2)

January 7, 2011

Photo #1-Runway 11



Photo #2 - Runway 29



January 7, 2011

2. Primary Surface Administrative Code 450-9-1-.12(2)

State Licensing Standards:

Primary Surface (See Appendix 1): The primary surface is 250 feet wide, centered on the runway centerline and extends 200 feet past the end of the marked runway. The primary surface is required to be free of all obstructions, manmade or natural. The only allowable objects are runway lights, guidance signs, or navigation equipment that by function is required to be within the primary surface boundaries.

Inspection Results:

The primary surface meets state requirements (Photo # 3).

3. Runway Safety Area Administrative Code 450-9-1-.12(3)

State Licensing Standards:

• Runway Safety Area (Appendix 1): All runways are required to maintain an obstruction free area adjacent to each runway. This area is 120 feet wide, centered on the runway centerline, and extends for a distance of 200 feet past the runway end. The area must be compacted and graded smooth with no ruts, humps, depressions or other potentially hazardous surface variations. The slope along the longitudinal centerline shall not exceed a rise or fall of three percent in elevation relative to the runway end elevation. The lip from the top of the pavement to the grade adjacent to the runway should not exceed 3 inches.

Inspection Results:

 The grade of the runway safety area meets state requirements (Photo # 3).

January 7, 2011

Photo #3 - Primary Surface and Safety Area



4. Airport Markings Administrative Code 450-9-1-.12(4)

State Licensing Standards:

 Airport Markings: All runways are required to be marked in a manner identifying the boundaries of the landing areas. The runway markings must be painted white and be maintained in a legible condition.

Inspection Results

• All airport markings and signage are in good condition (Photo # 4).

January 7, 2011

Photo #4 - Non-Precision Instrument Approach Markings



5. Wind Direction Indicator Administrative Code 450-9-1-.12(5)

State Licensing Standards:

 Wind Direction Indicators: All airports are required to have an operational wind direction indicator. It must be installed in a highly visible area and free from obstructions to ensure true wind direction and velocity. Night operations require the indicator be lighted.

Inspection Results:

• The wind direction indicator (wind cone) is operational and in good condition (Photo # 5).

January 7, 2011





6. Airport Lighting Administrative Code 450-9-1-.12(6)

State Licensing Standards:

 Airport Lighting: Runway lights and a lighted wind direction indicator are required for night operations. A rotating beacon is suggested. All runway, threshold, and taxiway lighting shall be maintained in operational condition and shall not be obscured by natural growth such as grass and/or weeds.

Inspection Results:

- The airport lighting system was inspected and found operational with the following exceptions:
 - Threshold Lights 0 inoperative
 - Runway Lights 0 inoperative
 - Taxiway Lights 0 inoperative
 - REIL 0 inoperative
 - PAPI 0 inoperative

January 7, 2011

7. Runway, Taxiway and Apron Conditions Administrative Code 450-9-1-.12(7)

State Licensing Standards:

• Runway, Taxiway and Apron Conditions: All airport pavement surfaces associated with aircraft operations must be kept smooth and free of any defect or obstruction that could damage an aircraft. The lip of the airport pavement surfaces must not exceed three (3) inches in elevation from the top of the pavement to the shoulder. The drop should only be enough to allow sufficient drainage and not pose a control problem for aircraft exiting the runway. The aircraft parking apron is for the operation and parking of aircraft only and should be smooth and free of obstructions or defects that could cause damage to aircraft during operations.

Inspection Results:

 The airport surfaces are in good condition; however there is a lateral undulation located just prior to runway 29's first taxiway and before reaching where the recent runway extension ties into the existing pavement.

Maintenance Required:

 The airport's consultant's engineers should determine the extent of the anomaly and monitor it, to insure the irregularity does not become a hazard.

8. Fueling Area Requirements Administrative Code 450-9-1-.12(8)

State Licensing Standards:

- Signs should be posted prohibiting open flames or smoking in fueling areas. The fueling facility must be labeled indicating the type fuel being dispensed.
- Grounding cables must be available.
- A fire extinguisher approved for the purpose of extinguishing petroleum product fires available during all fueling operations.
- Serviceable hoses and connections that would preclude a rupture or leaking of fuel.

January 7, 2011

Inspection Results:

 The fueling area meets the requirements established by the Alabama Department of Transportation. However, the State of Alabama Department of Agriculture and Industries may have additional requirements for fueling systems that were not considered during this inspection (Photo # 6).





9. Prohibited Activities Administrative Code 450-9-1-.16

State Licensing Standards:

 Prohibited Activities: The use of any portion of the aircraft operations area, or airport property within the boundaries of the imaginary surfaces of a licensed airport for any purpose other than the operation of aircraft shall be deemed a non-aeronautical activity and is prohibited.

January 7, 2011

Inspection Results:

• No prohibited activities were observed during the inspection.

Summary:

The table below summarizes items noted in this report.

INSPECTION SUMMARY


Inspection Area	Violation/Maintenance	Corrective Action	
Airport Surfaces	Maintenance	Measure and monitor	
		anomaly on runway 29	


Included with this report is an airport safety self-inspection checklist. This checklist is taken from FAA Advisory Circular (AC) 150/5200-18C and should be used in accordance with this AC to develop your own self-inspection program.

Please contact the Aeronautics Bureau of the Alabama Department of Transportation at (334) 242-6820 with questions concerning the Annual Inspection Report.

January 7, 2011

Approach and Departure Path Dimensions						
Inner Outer						
Width	Width	Length Acreage				
250 Feet 450 Feet 1,000 Feet 8.04 Acres						
	Primary Surface Dimensions					
250 Feet Wide Centered Along Runway Centerline						
Extending 200 Feet Past the Runway End						
Runway Safety Area Dimensions						
120 Feet Wide Centered Along Runway Centerline						
Extending 200 Feet Past the Runway End						





APPENDIX 1

AIRPORT SAFETY SELF-INSPECTION CHECKLIST

DATE:	DAY:			√ Satisf	actory
Day Inspector/Time:	Night I	nspect	or/Tim		tisfactory
					RESOLVED BY
FACILITIES	CONDITIONS	D	N	REMARKS	(Date/Initials)

Day Inspector/Time: Night Inspector/Time:					
FACILITIES	CONDITIONS	D	N	REMARKS	RESOLVED BY (Date/Initials)
	Pavement lips over 3"				
	Hole – 5" diam. 3" deep				
	Cracks/spalling/heaves				
Pavement Areas	FOD: gravel/debris/sand				
	Rubber deposits				
	Ponding/edge dams				
	75				
	Ruts/humps/erosion				
	Drainage/construction				
	Support equipment/aircraft				
Safety Areas	Frangible bases				
	Unauthorized objects				
	Clearly visible/standard				
	Runway markings				
	Taxiway markings				
Markings	Holding position markings				
	Glass beads				
	Standard/meet Sign Plan				
	Obscured/operable				
Signs	Damaged/retroreflective				

FACILITIES	CONDITIONS Obscured/dirty/operable Damaged/missing Faulty aim/adjustment Runway lighting Taxiway lighting Pilot control lighting	D	N	REMARKS	RESOLVED BY (Date/Initials)
Navigational Aids	Rotating beacon operable Wind indicators RENLs/VGSI systems				
Obstructions	Obstruction lights operable Cranes/trees				
Fueling Operations	Fencing/gates/signs Fuel marking/labeling Fire extinguishers Frayed wires Fuel leaks/vegetation				
Snow & Ice	Surface conditions Snowbank clearances Lights & signs obscured NAVAIDs Fire access				

FACILITIES	CONDITIONS	D	N	REMARKS	RESOLVED BY (Date/Initials)
	Barricades/lights				
	Equipment parking				
Construction	Material stockpiles				
	Confusing signs/markings				
	Equipment/crew availability				
Aircraft Rescue	Communications/alarms				
and Fire Fighting	Response routes affected				
					9
	Fencing/gates/signs				
Public Protection	Jet blast problems				
	Wildlife present/location				
Wildlife Hazards	Complying with WHMP				
Wildlife Hazarus	Dead birds				
Comments/Remarks:					